

# Duralay Heatflow 3 mm: 11 x 1.37 m (15.07 m<sup>2</sup>)

Art. nr - 114100110

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

A specialized underlayment with low thermal resistance, providing a warm feel to any floor. Suitable for laminate and parquet. Duralay Heatflow underlays all feature lower thermal resistance, allowing warmth generated by underfloor heating to quickly permeate the room. They conduct more heat than other underlays, making them the ideal choice for underfloor heating systems, resulting in enhanced heating capacity and potential energy savings. The unique production techniques by Interfloor enable the manufacturing of underlays with higher thermal conductivity and thus lower resistance than standard options, while maintaining essential qualities of comfort and floor protection. The low thermal resistance makes it ideal for wood and laminate floors combined with underfloor heating. Resilient high-density rubber reduces sound within the room and prevents overload of the joints in wood and laminate flooring.

# Duralay Heatflow 3 mm: 11 x 1.37 m (15.07 m<sup>2</sup>)

Art. nr - 114100110

## Specifications

Floor type	Parquet / Laminate
Product weight	2407 g/m <sup>2</sup>
Product dimensions (Length)	11 m
Product dimensions Width (Unit)	m
Product dimensions in m2	15.07 m <sup>2</sup>
Base unit	Roll
Thickness	3 mm
Density	802 kg/m <sup>3</sup>
Brand	Duralay
Laying method	Floating
Material	Sponge rubber
Product dimensions (Unit)	m <sup>2</sup>
TOG rating	0.35 TOG
Thermal resistance - R-value	0.035 m <sup>2</sup> K/W
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Project use	Yes
CS	CS4
CS/CC (compressive Strength / Compressive Creep)	400 kPa

# Duralay Heatflow 3 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 114100110



Sound-reducing - Lw	21 dB Lw
CS/CC (Compressive Strength / Compressive Creep)	400 kPa
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed

# Duralay Heatflow 3 mm: 11 x 1.37 m (15.07 m<sup>2</sup>)

Art. nr - 114100110

**estillon**  
WE WILL IMPROVE YOUR FLOOR

