

Duralay Heatflow 3 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 114100110

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

A specialist underlay with low thermal resistance. It provides a warm feeling under every type of floor.

Key benefits:

- Suitable for laminate and parquet flooring.
- Low thermal resistance across all Duralay Heatflow underlays, so heat from underfloor heating quickly spreads throughout the room.

Duralay Heatflow 3 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 114100110



- Higher heat conduction than many other solutions, making it ideal for underfloor heating installations.
- Higher heating capacity and lower energy consumption.
- Manufactured using Interfloor's production techniques for higher thermal conductivity and lower thermal resistance.
- Comfort and floor protection are maintained.
- Ideal for wood and laminate floors in combination with underfloor heating.
- Resilient, high-density rubber reduces noise within the room.
- Helps prevent overloading of the joints in wood and laminate floors.

Duralay Heatflow 3 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 114100110

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

| | |
|--|--------------------------|
| Floor type | Parquet / Laminate |
| Product weight | 2407 g/m ² |
| Product dimensions (Length) | 11 m |
| Product dimensions (Width) | 1.37 m |
| Product dimensions in m ² | 15.07 m ² |
| Base unit | Roll |
| Thickness | 3 mm |
| Density | 802 kg/m ³ |
| Material | Sponge rubber |
| Brand | Duralay |
| Thermal resistance - R-value | 0.035 m ² K/W |
| TOG rating | 0.35 TOG |
| Suitable for underfloor heating | Yes |
| Suitable for floor cooling | Yes |
| CS | CS4 |
| CS/CC (compressive Strength / Compressive Creep) | 400 kPa |
| Domestic use | Yes |
| Project use | Yes |
| Laying method | Floating |
| Product dimensions (Unit) | m ² |

Duralay Heatflow 3 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 114100110

estillon
WE WILL IMPROVE YOUR FLOOR

| | |
|--|--|
| Type of base floor | Wooden floor / Fixed sand cement floor / Floating screed |
| Sound-reducing - ΔLw | 21 dB ΔLw |
| CS/CC (Compressive Strength / Compressive Creep) | 400 kPa |

Duralay Heatflow 3 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 114100110

estillon
WE WILL IMPROVE YOUR FLOOR

