

Duralay Heatflow 6,1 mm: 7,3 x 1,37 m (10 m²)

Art. nr - 114100117

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

A specialized underlay with low thermal resistance that gives a warm feel to any floor. Duralay Heatflow underlays have a lower thermal resistance, allowing heat generated by underfloor heating to enter the room quickly. They conduct more heat than other underlays, making them an ideal choice for underfloor heating installations, providing greater heating capacity and a lower energy consumption.

Interfloor's unique production techniques enable them to produce underlays with higher thermal conductivity and thus lower thermal resistance than usual, while maintaining essential qualities of floor comfort and protection. The low thermal resistance makes it perfect for wood and laminate floors in conjunction with underfloor heating.

Duralay Heatflow 6,1 mm: 7,3 x 1,37 m (10 m2)

Art. nr - 114100117



- Sponge rubber underlay for excellent floor comfort
- Extends the lifespan of the carpet

Duralay Heatflow 6,1 mm: 7,3 x 1,37 m (10 m2)

Art. nr - 114100117

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Floor type	Carpet
Thickness	6.1 mm (10% margin)
Product weight	3017 g/m ² (10% margin)
Density	495 kg/m ³ (10% margin)
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Domestic use	Yes
Project use	Yes
Sound-reducing - ΔL_w	31 dB ΔL_w
TOG rating	0.75 TOG
Thermal resistance - R-value	0.075 m ² K/W
Brand	Duralay
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Laying method	Taut
Product dimensions (Length)	7.3 m (10% margin)
Product dimensions (Width)	1.37 m
Product dimensions in m2	10 m ²
Base unit	Roll
Material	Sponge rubber

Duralay Heatflow 6,1 mm: 7,3 x 1,37 m (10 m²)

Art. nr - 114100117

estillon
WE WILL IMPROVE YOUR FLOOR

