

# Duralay Heatflow 6.1 mm: 7.3 x 1.37 m (10 m<sup>2</sup>)

Art. nr - 114100117

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

A specialized underlay with low thermal resistance that gives a warm feel to any floor. Duralay Heatflow underlays have a lower thermal resistance, allowing heat generated by underfloor heating to enter the room quickly. They conduct more heat than other underlays, making them an ideal choice for underfloor heating installations, providing greater heating capacity and a lower energy consumption.

Interfloor's unique production techniques enable them to produce underlays with higher thermal conductivity and thus lower thermal resistance than usual, while maintaining essential qualities of floor comfort and protection. The low thermal resistance makes it perfect for wood and laminate floors in conjunction with underfloor heating.

# Duralay Heatflow 6.1 mm: 7.3 x 1.37 m (10 m<sup>2</sup>)

Art. nr - 114100117



- Sponge rubber underlay for excellent floor comfort
- Extends the lifespan of the carpet

# Duralay Heatflow 6.1 mm: 7.3 x 1.37 m (10 m<sup>2</sup>)

Art. nr - 114100117

**estillon**  
WE WILL IMPROVE YOUR FLOOR

## Specifications

Floor type	Carpet
Product weight	3017 g/m <sup>2</sup> (10% margin)
Product dimensions (Length)	7.3 m (10% margin)
Product dimensions (Width)	1.37 m
Product dimensions in m2	10 m <sup>2</sup>
Base unit	Roll
Thickness	6.1 mm (10% margin)
Density	495 kg/m <sup>3</sup> (10% margin)
Material	Sponge rubber
Brand	Duralay
TOG rating	0.75 TOG
Thermal resistance - R-value	0.075 m <sup>2</sup> K/W
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Project use	Yes
Laying method	Taut
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Sound-reducing - ΔLw	31 dB ΔLw

# Duralay Heatflow 6.1 mm: 7.3 x 1.37 m (10 m<sup>2</sup>)

Art. nr - 114100117

**estillon**  
WE WILL IMPROVE YOUR FLOOR

