
Duralay LVT Dry-Back 1.8 mm: 6.5 x 1 m (6.5 m²)

Art. nr - 114100122

Scan this QR code to view this product on our website.



Description

Duralay LVT Dry-Back Underlay is a versatile solution designed for installing 'dry back' LVT flooring. It significantly reduces the preparation time of the subfloor. Installation is quick, clean, and easy. The underlay is laid loose over the existing floor. The film is peeled back to expose the adhesive, after which the new floor is positioned onto the 'high grip' layer of the underlay. - Suitable for 'dry back' LVT flooring - Unique self-adhesive backing - Significantly shorter installation times and costs - Quick to install, easy to handle - Preparation time for the subfloor is greatly reduced

Duralay LVT Dry-Back 1.8 mm: 6.5 x 1 m (6.5 m²)

Art. nr - 114100122

Specifications

Floor type	LVT Dryback
Thickness	1.8 mm
Type of base floor	Fixed sand cement floor / Floating screed
Domestic use	Yes
Project use	Yes
PC (Punctual Conformability)	0.55 mm
CS	CS4
CS/CC (compressive Strength / Compressive Creep)	450 kPa
Product weight	2600 g/m²
Product dimensions (Length)	6.5 m
Product dimensions (Width)	1 m
Product dimensions in m2	6.5 m²
Sound-reducing - ΔLw	15 dB ΔLw
TOG rating	0.1 TOG
Thermal resistance - R-value	0.01 m² K/W
RWS (Radiated Walking Sound (reduction)	up to 6 %
RLB (Resistance to Large Ball)	~ 750 mm
DL (Dynamic Load)	>100,000 cycles
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Fire classification	Bfl-s1

Duralay LVT Dry-Back 1.8 mm: 6.5 x 1 m (6.5 m²)

Art. nr - 114100122

Density	1444 kg/m³
Material	Sponge rubber
Brand	Duralay
Laying method	Floating
CS/CC (Compressive Strength / Compressive Creep)	450 kPa

Duralay LVT Dry-Back 1.8 mm: 6.5 x 1 m (6.5 m²)

Art. nr - 114100122









