

Duralay Silentfl. Plus2 3 mm: 1,37m x 7,29 (10 m2)

Art. nr - 114100123

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Sound-reducing underlayment with an integrated vapor barrier.

- Suitable for floating installation of laminate and parquet
- Resilient high-density rubber
- Excellent acoustic improvement
- Conceals small imperfections in the surface

Duralay Silentfl. Plus2 3 mm: 1,37m x 7,29 (10 m2)

Art. nr - 114100123

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Floor type	Parquet / Laminate
Thickness	3 mm
Type of base floor	Fixed sand cement floor / Floating screed
Domestic use	Yes
CS	CS1
CS/CC (compressive Strength / Compressive Creep)	150 kPa
Sound-reducing - ΔL_{lin}	10 dB ΔL_{lin}
Product weight	2204 g/m ²
Product dimensions (Length)	7.3 m
Product dimensions (Width)	1.37 m
Product dimensions in m ²	10 m ²
Sound-reducing - ΔL_w	20 dB ΔL_w
TOG rating	0.38 TOG
Thermal resistance - R-value	0.38 m ² K/W
TUV certificate	Yes
DIBT certificate	Z-158.10-260
Suitable for underfloor heating	Yes
Sound-reducing - ΔL_{lin} - Test method	ISO 10140 / ISO 717-2
Sound-reducing - ΔL_w - Test method	ISO 10140 / ISO 717-2
Flame-retardant	Cfl-S1
Density	735 kg/m ³

Duralay Silentfl. Plus2 3 mm: 1,37m x 7,29 (10 m2)

Art. nr - 114100123



Material	Sponge rubber
Brand	Duralay
Laying method	Floating
CS/CC (Compressive Strength / Compressive Creep)	150 kPa

Duralay Silentfl. Plus2 3 mm: 1,37m x 7,29 (10 m2)

Art. nr - 114100123

estillon
WE WILL IMPROVE YOUR FLOOR

