

# Royale 600 6 mm: 7.52 x 1.33 m (10 m<sup>2</sup>)

Art. nr - 114107600

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

A durable yet comfortable underlay suitable for stretch fit installations.

- Ideal for stretch-fit carpet installation
- Flat sponge rubber
- HC/U, Heavy contract use

# Royale 600 6 mm: 7.52 x 1.33 m (10 m<sup>2</sup>)

Art. nr - 114107600

## Specifications

Floor type	Carpet
Product weight	2983 g/m <sup>2</sup> (10% margin)
Product dimensions (Length)	7.52 m (10% margin)
Product dimensions (Width)	1.33 m
Product dimensions in m2	10 m <sup>2</sup>
Base unit	Roll
Thickness	6 mm (10% margin)
Density	497 kg/m <sup>3</sup> (10% margin)
Material	Sponge rubber with flat structure
Brand	Tredaire
TOG rating	0.7 TOG
Thermal resistance - R-value	0.07 m <sup>2</sup> K/W
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Project use	Yes
Laying method	Stretching
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Sound-reducing - ΔLw	30 dB ΔLw
Flame-retardant	Bfl-S1
Flame-retardant - Test method	EN 13501-1 (2018)

# Royale 600 6 mm: 7.52 x 1.33 m (10 m<sup>2</sup>)

Art. nr - 114107600

**estillon**  
WE WILL IMPROVE YOUR FLOOR

