

Tredaire Flamecheck 6 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 114107806

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Tredaire Flamecheck is an IMO fire-retardant underlay ideal for ships, offshore installations, hotels, and any location where flame retardancy is essential.

- IMO fire-retardant underlay
- Suitable for double-stick and stretch-fit carpet installation
- Recycled polyurethane foam (PU)

PLEASE NOTE: In order to conform to test certification, the underlay must be fitted print side up, and adhered to the subfloor.

Tredaire Flamecheck 6 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 114107806

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Floor type	Carpet
Product weight	928 g/m ² (10% margin)
Product dimensions (Length)	11 m (10% margin)
Product dimensions (Width)	1.37 m
Product dimensions in m ²	15.07 m ²
Base unit	Roll
Thickness	6 mm (10% margin)
Density	145 kg/m ³ (10% margin)
Material	Top layer: Orange polyethylene film Middle layer: Rebond Polyurethane foam Bottom layer: Flame retardant non-woven scrim and clear polyethylene film
Brand	Tredaire
TOG rating	1.58 TOG
Thermal resistance - R-value	0.158 m ² K/W
Suitable for underfloor heating	Yes
Domestic use	Yes
Project use	Yes
Laying method	Stretching / double-sided gluing
IMO certificate	Yes

Tredaire Flamecheck 6 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 114107806






Green choice label	Yes
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Sound-reducing - ΔL_w	30 dB ΔL_w

Tredaire Flamecheck 6 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 114107806

estillon
WE WILL IMPROVE YOUR FLOOR



estillon
GREEN CHOICE

