Sonixx Soundsure 560 5,6 mm: 7,3 x 1,37 m (10 m2)

Art. nr - 114107825

Scan this QR code to view this product on our website.



Description

Soundsure 560 is an acoustic layer for use beneath the screed, for example in a floating screed construction. The layer is designed to reduce the transmission of
sound through the floor construction and contributes to a quieter, more comfortable building performance. This is especially relevant in projects where acoustics and predictable handover quality are important, such as multi-storey residential buildings and commercial buildings.

In addition, Soundsure 560 can also be used as an underlay on top of the screed, directly beneath the floor finish, when you want to add extra acoustic comfort and stability within the overall floor build-up during the finishing phase.

- Acoustic improvement in floor build-ups with (floating) screeds
- Also suitable as an underlay on top of the screed, directly beneath the floor finish
- Suitable for commercial applications with high usage loads
- Durable base layer within the overall floor construction
- Practical to install within the floor build-up

Sonixx Soundsure 560 5,6 mm: 7,3 x 1,37 m (10 m2)

Art. nr - 114107825

Specifications

Thickness	5,6 mm
Domestic use	Yes
Product weight	2240 gr/m²
Product dimensions (Length)	7,3 m
Product dimensions (Width)	1,37 m
Product dimensions (unit)	m²
Sound-reducing - ΔLw	27 dB ΔLw
TOG rating	1,01 TOG
Thermal resistance - R-value	0,101 m² K/W
Density	400 kg/m³
Material	Crumb rubber
Brand	Sonixx
Laying method	Floating
Installation instruction explanation	Perpendicular to the laying direction of the top floor. Prevent the seams of the underlay and the top floor from aligning.

Sonixx Soundsure 560 5,6 mm: 7,3 x 1,37 m (10 m2)

Art. nr - 114107825

