

Egalsoft 6.5 mm: 22 x 1.37 m (30.14 m²)

Art. nr - 68240

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Installation instruction

- Let the underlay, like the carpet to be installed, acclimatize for at least 24 hours in the closed packaging in the room where it will be installed.
- The ideal humidity for a carpet installation is between 50–70% and the working temperature is 15–20 degrees Celsius.
- Work cleanly and ensure that the substrate is completely free from grit, dust, and dry before installation.
- For cutting the underlay, we recommend a standard trapezoid (snap-off) knife or carpet shears.
- Use a roller with a maximum weight of 30 kg to fix it to the substrate.
- An underlay cannot prevent the natural movement of a carpet; therefore, we recommend always double-sided gluing for carpets that are sensitive to shrinkage.

Egalsoft 6.5 mm: 22 x 1.37 m (30.14 m²)

Art. nr - 68240

- It's advisable to additionally glue Egalsoft along the edges over 10 cm at the bottom with universal carpet glue to accommodate any shrinkage.
- Always follow the installation advice of the carpet manufacturer and adhesive supplier to avoid problems during installation.

Top side

With the anti-slip layer facing downwards.

Disclaimer

If the installation instructions are not followed, Estillon cannot be held liable for damage and/or claims arising from incorrect installation. If in doubt, always consult your supplier.