

Egalsoft FR 6 mm: 22 x 1,37 m (30,14 m²)

Art. nr - 68244

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Installation instruction

- Acclimate the underlay, just like the carpet to be installed, for at least 24 hours in the closed packaging in the room where it will be installed.
- The ideal humidity for carpet installation is between 50–70% and the processing temperature is 15–20 degrees Celsius.
- Work cleanly and ensure that the substrate is completely free of debris, dust-free, and dry before installation.
- For cutting the underlay, we recommend a standard trapezoidal (snap-off) blade knife or carpet scissors.
- Use a roller with a maximum weight of 30 kg for fixing on the substrate.
- An underlay cannot prevent the natural movement of a carpet; therefore, we recommend always double gluing shrink-sensitive carpets.

Egalsoft FR 6 mm: 22 x 1,37 m (30,14 m²)

Art. nr - 68244

- It is advisable to further glue Egalsoft on the underside over 10 cm along the edges with universal carpet glue to absorb any shrinkage.
- Always follow the installation advice of the carpet manufacturer and adhesive supplier to avoid installation issues.
- For project use, apply an anti-slip fixing agent under the underlay for additional stability.

Top side

With the anti-slip layer facing downwards.

Disclaimer

If the installation instructions are not followed, Estillon cannot be held liable for damage and/or claims arising from incorrect installation. If in doubt, always consult your supplier.