

Egalfloor Fini 5 mm: 22 x 80 x 57 cm (10,03 m²)

Art. nr - 62072

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Egalfloor Fini is a high-quality softboard made of needle felt reinforced with bitumen, perfect for the floating installation of laminate, parquet, and vinyl in homes. Easy and quick to install. High impact resistance. Leveling unevenness, insulating cold floors. Good sound insulation. Applicable with underfloor heating. Extends the lifespan of vinyl. Enhances the walking comfort of your laminate, parquet, and vinyl.

Egalfloor Fini 5 mm: 22 x 80 x 57 cm (10,03 m²)

Art. nr - 62072

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Floor type	Vinyl / Laminate / Parquet
Thickness	5 mm
Type of base floor	Fixed sand cement floor / Floating screed
Domestic use	Yes
PC (Punctual Conformability)	> 0.5mm
Bending strength (Test method: EN 310)	1.2 N/mm ²
Product weight	1500 g/m ²
Product dimensions (Length)	800 mm
Product dimensions (Width)	570 mm
Product dimensions in m2	10.03 m ²
Sound-reducing - ΔL_w	18 dB ΔL_w
TOG rating	0.71 TOG
Thermal resistance - R-value	0.071 m ² K/W
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Moisture content (Test method: EN 322)	\pm 6-12 %
Durability / Thickness swelling after 2 hours (Test method: EN 317)	6
Durability / Thickness swelling after 2 hours - unit	%
Sound-reducing - ΔL_w - Test method	NEN-EN ISO 140-8
Thermal resistance - Test method	ISO 8302

Egalfloor Fini 5 mm: 22 x 80 x 57 cm (10,03 m²)

Art. nr - 62072

Flame-retardant	Efl-S1
Flame-retardant - Test method	EN 13501-1
Density	300 kg/m ³
Material	30% birch, 60% softwood fibres, 10% bitumen
Brand	Egalfloor
Formaldehyde (Test method: EN 120)	E-1
Laying method	Floating
Wheelchair load (Test method: EN 985)	Suitable

Egalfloor Fini 5 mm: 22 x 80 x 57 cm (10,03 m²)

Art. nr - 62072

estillon
WE WILL IMPROVE YOUR FLOOR

