

Floorfixx fini 8 mm: 10 x 85 x 59 cm (5,015 m²)

Art. nr - 62074

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Floorfixx fini is an underlay system that absorbs small irregularities in the subfloor. Using the self-adhesive lip-seam connection, you can quickly and easily create a new, insulating, and level subfloor that can be loaded immediately. Floorfixx fini is suitable for residential and light project applications. It renovates poor basic floors for LVT Click, vinyl, and LVT Rigid with underlay.

- No waiting/drying times and can be loaded immediately
- Self-adhesive lip-seam connection
- Levels out irregularities
- Maximum stability

Floorfixx fini 8 mm: 10 x 85 x 59 cm (5,015 m²)

Art. nr - 62074



- Extends the lifespan of the finished floors
- Insulates impact sound and meets the 10dB standard set by the VvE

Floorfixx fini 8 mm: 10 x 85 x 59 cm (5,015 m²)

Art. nr - 62074

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Thickness	8 mm (10% margin)
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Sound-reducing - ΔL_{lin}	10 dB ΔL_{lin}
Sound-reducing - ΔL_w - Test method	ISO 10140 / ISO 717-2
TUV certificate	Yes
Flame-retardant	Efl-S1
Product dimensions (Width)	590 mm (10% margin)
Product dimensions (Length)	850 mm (10% margin)
Product dimensions in m ²	5,015 m ²
Density	319 kg/m ³ (10% margin)
Product weight	2552 gr/m ² (10% margin)
Base unit	Pack
Brand	Floorfixx
Formaldehyde (Test method: EN 120)	E-1
Leveling capacity	Good
Thermal resistance R-value - unit	m ² K/W
Thermal resistance - Test method	ISO 8302
TOG rating	2,13 TOG
PC (Punctual Conformability)	12
CS	CS1

Floorfixx fini 8 mm: 10 x 85 x 59 cm (5,015 m²)

Art. nr - 62074

estillon
WE WILL IMPROVE YOUR FLOOR

CS/CC (compressive Strength / Compressive Creep)	149 kPa
Domestic use	Yes
Project use	Yes
Laying method	Floating
Bending strength (Test method: EN 310)	39 N/mm ²
Wheelchair load (Test method: EN 985)	Suitable
Flame-retardant - Test method	EN 13501-1
CS/CC (Compressive Strength / Compressive Creep)	149 kPa

Floorfixx fini 8 mm: 10 x 85 x 59 cm (5,015 m²)

Art. nr - 62074

estillon
WE WILL IMPROVE YOUR FLOOR

