

# Egalfloor 5 mm: 79 x 59 cm (6.99 m<sup>2</sup>)

Art. nr - 62081

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Egalfloor 5 mm is a premium softboard made from softwood, perfect for floating laminate and parquet installation at home. - Easy and quick to lay - High impact resistance - Levels uneven surfaces and insulates cold floors - Good contact insulation - Applicable with underfloor heating

# Egalfloor 5 mm: 79 x 59 cm (6.99 m<sup>2</sup>)

Art. nr - 62081

## Specifications

|  |   |
|--|---|
| Floor type                             | Laminate / Parquet                        |
| Base unit                              | Pack                                      |
| Product weight                         | 1250 g/m <sup>2</sup>                     |
| Product dimensions (Length)            | 790 mm                                    |
| Product dimensions in m2               | 6.99                                      |
| Thickness                              | 5 mm                                      |
| Density                                | 250 kg/m <sup>3</sup>                     |
| Material                               | 100% wood fibers (softwood)               |
| Brand                                  | Egalfloor                                 |
| Moisture content (Test method: EN 322) | ± 6-12 %                                  |
| Formaldehyde (Test method: EN 120)     | E-1                                       |
| TOG rating                             | 0.71 TOG                                  |
| Suitable for underfloor heating        | Yes                                       |
| SD (Steam Diffusion)                   | 0.02m                                     |
| Domestic use                           | Yes                                       |
| Laying method                          | Floating                                  |
| Product dimensions (Width)             | 590 mm                                    |
| Product dimensions (Unit)              | m <sup>2</sup>                            |
| Type of base floor                     | Fixed sand cement floor / Floating screed |
| Bending strength (Test method: EN 310) | 1.2 N/mm <sup>2</sup>                     |

# Egalfloor 5 mm: 79 x 59 cm (6.99 m<sup>2</sup>)

Art. nr - 62081

|   |  |
|---|--|
| Durability / Thickness swelling after 2 hours (Test method: EN 317) | 6  |
| Durability / Thickness swelling after 2 hours - unit                | %  |
| Wheelchair load (Test method: EN 985)                               | Suitable   |
| Thermal resistance - R-value (Test method: ISO 8302)                | 0.071 m <sup>2</sup> K/W   |
| Sound-reducing L <sub>w</sub> (Test method: NEN-EN ISO 717-2)       | 18 dB L <sub>w</sub>   |
| Flame-retardant (Test method: EN 13501-1)                           | Efl-S1   |
| Laying direction  | Install softboard floating in a half-brick bond on a moisture barrier. |
| Suitable for floor cooling  | Yes  |

# Egalfloor 5 mm: 79 x 59 cm (6.99 m<sup>2</sup>)

Art. nr - 62081

**estillon**  
WE WILL IMPROVE YOUR FLOOR

