

Floorfixx smart 8 mm: 82,5 x 56,5 cm (2,80 m²)

Art. nr - 62104

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

The Floorfixx smart is an innovative underlayment system that utilizes a convenient tongue-and-groove connection to create an insulating, flat, and immediately load-bearing surface. It is perfect for both residential and commercial uses. Also, use the Floorfixx smart edge strips for a perfect start on the first row. It is designed for renovating poor subfloors with a minimum top layer thickness of 2.5 mm, including LVT Dryback, LVT Click, vinyl, carpet tiles, LVT Rigid with underlayment, and linoleum.

- No waiting or drying times are required, ready to bear loads immediately
- It levels out imperfections
- Provides maximum stability

Floorfixx smart 8 mm: 82,5 x 56,5 cm (2,80 m²)

Art. nr - 62104



- Complying with the 10 dB sound insulation standard set by the homeowners' association

Floorfixx smart 8 mm: 82,5 x 56,5 cm (2,80 m²)

Art. nr - 62104

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Thickness	8 mm (10% margin)
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Sound-reducing - ΔL_{lin}	10 dB ΔL_{lin}
Sound-reducing - ΔL_w - Test method	EN 13501-1:2007 + A1:2009
TUV certificate	Yes
Flame-retardant	Bfl-S1
Product dimensions (Width)	56.5 cm (10% margin)
Product dimensions (Length)	82.5 cm (10% margin)
Product dimensions in m ²	2.8 m ²
Density	610 kg/m ³ (10% margin)
Product weight	4881 g/m ² (10% margin)
Base unit	Pack
Material	Top layer: 3 mm MDF Bottom layer: 3 mm MDF & 2.2 mm XPS foam
Brand	Floorfixx
Formaldehyde (Test method: EN 120)	E-1
Leveling capacity	2 mm over 2 m length
Thermal resistance R-value - unit	m ² K/W
Thermal resistance - Test method	ISO 8302
TOG rating	1.23 TOG
Suitable for underfloor heating	Yes

Floorfixx smart 8 mm: 82,5 x 56,5 cm (2,80 m²)

Art. nr - 62104

PC (Punctual Conformability)	12
CS	CS2
CS/CC (compressive Strength / Compressive Creep)	240 kPa
Domestic use	Yes
Project use	Yes
Laying method	Floating
Bending strength (Test method: EN 310)	40 N/mm ²
Wheelchair load (Test method: EN 985)	Suitable
Flame-retardant - Test method	EN 13501-1
CS/CC (Compressive Strength / Compressive Creep)	240 kPa
Hospitality Collection	Yes

Floorfixx smart 8 mm: 82,5 x 56,5 cm (2,80 m²)

Art. nr - 62104

estillon
WE WILL IMPROVE YOUR FLOOR

