

Floorfixx Optimum 8 mm 82.5 x 56.5 cm (2.80 m²)

Art. nr - 62107

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Floorfixx Optimum is an innovative self-adhesive underlayment system that does not require traditional glue. With its unique self-adhesive layer, you can quickly and easily create a new, insulating, and level subfloor that is instantly usable. Installation is straightforward thanks to the convenient tongue-and-groove connection. This system is suitable for both residential and commercial use. - Quick installation without traditional adhesives - Perfect for renovating unsuitable base floors for PVC Dryback planks and tiles - No waiting or drying times, immediately usable - Levels out imperfections and provides maximum stability - Ensures a smooth and flat base for your installation - Reduces impact noise and meets the VvE's 10dB standard.

Floorfixx Optimum 8 mm 82.5 x 56.5 cm (2.80 m²)

Art. nr - 62107

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Floor type	Carpet tiles / PVC Dryback
Base unit	Pack
Product weight	4714 g/m ²
Product dimensions (Length)	825 mm
Product dimensions in m2	2.8 m ²
Thickness	8 mm
Density	590 kg/m ³
Material	Top layer: 3 mm MDF & self-adhesive layer with silicone paper Bottom layer: 3 mm MDF & 2.2 mm XPS foam
Brand	Floorfixx
Formaldehyde (Test method: EN 120)	E-1
Leveling capacity	2 mm over 2 m length
TOG rating	1.23 TOG
Suitable for underfloor heating	Yes
CS	CS2
CS/CC (compressive Strength / Compressive Creep)	214
CS/CC (compressive Strength / Compressive Creep) - unit	kPa
Domestic use	Yes
Project use	Yes

Floorfixx Optimum 8 mm 82.5 x 56.5 cm (2.80 m²)

Art. nr - 62107

estillon
WE WILL IMPROVE YOUR FLOOR

Laying method	Floating
Product dimensions (Width)	565 mm
Product dimensions (Unit)	m ²
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Bending strength (Test method: EN 310)	40 N/mm ²
Wheelchair load (Test method: EN 985)	Suitable
Thermal resistance - R-value (Test method: ISO 8302)	0.123 m ² K/W
Sound-reducing (Test method: NEN-EN ISO 717-2)	10
Sound-reducing - unit	Llin
Sound-reducing Lw (Test method: NEN-EN ISO 717-2)	21 dB Lw
Flame-retardant (Test method: EN 13501-1)	Bfl-S1
CS/CC (Compressive Strength / Compressive Creep)	214
CS/CC (Compressive Strength / Compressive Creep) - unit	kPa
Laying direction	Floorfixx optimum is a self-adhesive underlayment system that is installed floating using the 75 mm lip seam connection.
TUV certificate	Yes

Floorfixx Optimum 8 mm 82.5 x 56.5 cm (2.80 m²)

Art. nr - 62107

estillon
WE WILL IMPROVE YOUR FLOOR

