

# Floorfixx comfort 10 mm: 120 x 60 cm (2.88 m<sup>2</sup>)

Art. nr - 62210

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Floorfixx comfort is an innovative underlayment system that uses a sandwich system and interactive adhesive to quickly and easily create a new, insulating, even, and immediately load-bearing floor. It is perfect for renovating poor subfloors and can be used beneath overlay materials that are at least 2 mm thick, such as LVT Dryback, LVT Click, carpet tiles, linoleum, vinyl, laminate flooring, and LVT Rigid with underlayment.

- No waiting or drying times □ immediately usable
- Levels unevenness up to 3 mm per linear meter
- Ensures maximum stability □ insulates impact noise and meets the 10 dB standard
- Developed for projects with high quality requirements and heavy traffic

# Floorfixx comfort 10 mm: 120 x 60 cm (2.88 m<sup>2</sup>)

Art. nr - 62210



- Suitable for use with underfloor heating and cooling

# Floorfixx comfort 10 mm: 120 x 60 cm (2.88 m<sup>2</sup>)

Art. nr - 62210

**estillon**  
WE WILL IMPROVE YOUR FLOOR

## Specifications

Floor type	LVT Dryback / LVT Click / Carpet tiles / Linoleum / Vinyl / Parquet / LVT Rigid with underlayment
Product weight	6535 g/m <sup>2</sup> (10% margin)
Product dimensions (Length)	120 cm (10% margin)
Product dimensions (Width)	60 cm (10% margin)
Product dimensions in m <sup>2</sup>	2.88 m <sup>2</sup>
Sound-reducing - $\Delta L_{lin}$	10 dB $\Delta L_{lin}$
Sound-reducing - $\Delta L_{lin}$ - Test method	ISO 10140 / ISO 717-2
Base unit	Pack
Thickness	10 mm (10% margin)
Density	653 kg/m <sup>3</sup> (10% margin)
Material	Top layer: 4 mm MDF / Bottom layer: 4 mm MDF & 2 mm perforated polyethylene
Brand	Floorfixx
Formaldehyde (Test method: EN 120)	E-1
Leveling capacity	3 mm over 1 m length
Thermal resistance - R-value	0.081 m <sup>2</sup> K/W
TOG rating	0.81 TOG
Thermal resistance - Test method	ISO 8302
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes

# Floorfixx comfort 10 mm: 120 x 60 cm (2.88 m<sup>2</sup>)

Art. nr - 62210

**estillon**  
WE WILL IMPROVE YOUR FLOOR

PC (Punctual Conformability)	12
CS	CS1
CS/CC (compressive Strength / Compressive Creep)	168 kPa
Domestic use	Yes
Project use	Yes
Laying method	Floating
DIBT certificate	Z-158.10-129
TUV certificate	Yes
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Bending strength (Test method: EN 310)	40 N/mm <sup>2</sup>
Wheelchair load (Test method: EN 985)	Suitable
Sound-reducing - $\Delta L_w$	20 dB $\Delta L_w$
Sound-reducing - $\Delta L_w$ - Test method	ISO 10140 / ISO 717-2
Flame-retardant	Bfl-S1
Flame-retardant - Test method	EN 13501-1
CS/CC (Compressive Strength / Compressive Creep)	168 kPa

# Floorfixx comfort 10 mm: 120 x 60 cm (2.88 m<sup>2</sup>)

Art. nr - 62210

**estillon**  
WE WILL IMPROVE YOUR FLOOR

