

Black Square 5 mm

Art. nr - 62280

Scan this QR code to view this product on our website.



Description

Black Square Underlayment 5 mm is a high-quality underlayment made of XPS foam. It is suitable for floating installation of laminate and parquet flooring in residential settings.

- Compression-resistant and lightweight
- 100% recyclable
- Levels uneven surfaces
- Improves thermal insulation
- Easy installation due to floating application and easy to cut
- Made from XPS foam
- Excellent sound insulation up to 10 dB, ΔL_{in} TÜV certified

Black Square 5 mm

Art. nr - 62280

Specifications

| | |
|---|---|
| Floor type | Parquet / Laminate |
| Product weight | 180 g/m ² |
| Product dimensions (Length) | 845 mm |
| Product dimensions (Width) | 585 mm |
| Product dimensions in m2 | 7.41 m ² |
| Sound-reducing - ΔL_{lin} | 10 dB ΔL_{lin} |
| Sound-reducing - ΔL_{lin} - Test method | EN-ISO 10140-1 - 5:2021 / EN-ISO 717-2:2021 |
| Base unit | Pack |
| Thickness | 5 mm |
| Density | 35 kg/m ³ |
| Material | XPS foam |
| Brand | Estillon |
| TOG rating | 1.92 TOG |
| Thermal resistance - R-value | 0.192 m ² K/W |
| Domestic use | Yes |
| Laying method | Floating |
| TUV certificate | Yes |
| Green choice label | Yes |
| Type of base floor | Fixed sand cement floor / Floating screed |
| Sound-reducing - ΔL_w | 21 dB ΔL_w |
| Sound-reducing - ΔL_w - Test method | EN-ISO 10140-1 - 5:2021 / EN-ISO 717-2:2021 |

Black Square 5 mm

Art. nr - 62280

