

# Luxerton Superior 3 mm: 75 x 155 cm (11.63 m<sup>2</sup>)

Art. nr - 67860

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Luxerton Superior is a non-slip underlay made from high-quality needle felt with a double-sided latex coating. It creates a comfortable and reliable base while preventing dangerous carpet movement. The product contains no plasticizers and is suitable for use on carpet, parquet, laminate, ceramics, marble, cork, and PVC, making it ideal for both residential and commercial use. Lightweight and easy to install. Even out small imperfections in the subfloor. Extends the lifespan and preserves the original appearance of the carpet. Environmentally friendly production and 100% recyclable. Compatible with underfloor heating.

# Luxerton Superior 3 mm: 75 x 155 cm (11.63 m<sup>2</sup>)

Art. nr - 67860

## Specifications

Floor type	Area rugs
Product weight	500 g/m <sup>2</sup>
Product dimensions (Length)	75 cm
Product dimensions Width (Unit)	cm
Product dimensions in m <sup>2</sup>	11.63 m <sup>2</sup>
Base unit	Pack
Thickness	3 mm
Density	167 kg/m <sup>3</sup>
Material	Top layer: Latex film with logo and pattern Middle layer: Polyester needle felt Bottom layer: Latex non-slip film
Brand	Luxerton
Thermal resistance - R-value	0.06 m <sup>2</sup> K/W
TOG rating	0.6 TOG
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Project use	Yes

# Luxerton Superior 3 mm: 75 x 155 cm (11.63 m<sup>2</sup>)

Art. nr - 67860

Laying method	Floating
Product dimensions (Unit)	m <sup>2</sup>
Type of base floor	Fixed sand cement floor / Floating screed
Flame-retardant	Cfl-S1
Flame-retardant - Test method	EN ISO 9239-1
Laying direction	Install Luxerton Superior under the carpet. Ensure that Luxerton Superior is at least 50mm smaller all around than the backing of the carpet.

# Luxerton Superior 3 mm: 75 x 155 cm (11.63 m<sup>2</sup>)

Art. nr - 67860

**estillon**  
WE WILL IMPROVE YOUR FLOOR

