

# Luxerton Superior 3 mm: 165 x 235 cm (38.78 m<sup>2</sup>)

Art. nr - 67862

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Luxerton Superior is a non-slip underlay crafted from high-quality needle felt with a dual-sided latex anti-slip coating. It creates a comfortable and reliable foundation and helps to prevent carpets from shifting dangerously. - Lightweight and easy to install - Levels out small imperfections in the subfloor - Extends the lifespan and preserves the original appearance of the carpet - Environmentally friendly production & 100% recyclable - Suitable for use with underfloor heating

# Luxerton Superior 3 mm: 165 x 235 cm (38.78 m<sup>2</sup>)

Art. nr - 67862

**estillon**  
WE WILL IMPROVE YOUR FLOOR

## Specifications

Floor type	Area rugs
Base unit	Pack
Product weight	500 g/m <sup>2</sup>
Product dimensions (Length)	165 cm
Product dimensions in m2	38.78 m <sup>2</sup>
Thickness	3 mm
Density	167 kg/m <sup>3</sup>
Material	Top layer: Latex film with logo and pattern Middle layer: Polyester needle felt Bottom layer: Latex non-slip film
Brand	Luxerton
TOG rating	0.60 TOG
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Project use	Yes
Laying method	Floating
Product dimensions (Width)	235 cm
Product dimensions (Unit)	m <sup>2</sup>
Type of base floor	Fixed sand cement floor / Floating screed

# Luxerton Superior 3 mm: 165 x 235 cm (38.78 m<sup>2</sup>)

Art. nr - 67862



Thermal resistance - R-value (Test method: ISO 8302)	0.060 m <sup>2</sup> K/W
Flame-retardant (Test method: EN 13501-1)	Cfl-S1
Laying direction	Install Luxerton Supreme under the carpet. Ensure that Luxerton Supreme is at least 50mm smaller all around than the backing of the carpet. When using Luxerton Supreme rolls, you need to remove the foil.

# Luxerton Superior 3 mm: 165 x 235 cm (38.78 m<sup>2</sup>)

Art. nr - 67862

**estillon**  
WE WILL IMPROVE YOUR FLOOR

