Luxerton Standard 2 mm: 60 x 130 cm (27.30 m²)

Art. nr - 68071

Scan this QR code to view this product on our website.

Description

Luxerton Standard is a lightweight non-slip underlay made from latex-impregnated needle felt. This underlay creates a stable foundation for any carpet and contains no plasticizers, enhancing the luxury and comfort of the carpet. It is suitable for use on carpet, parquet, laminate, ceramics, cork, and PVC. Lightweight and easy to install Fills in small imperfections in the subfloor Extends the lifespan and preserves the original appearance of the carpet Environmentally friendly production Compatible with underfloor heating







Specifications

Floor type	Area rugs
Base unit	Box
Product weight	150 g/m²
Product dimensions (Length)	60 cm
Product dimensions in m2	27.3 m ²
Thickness	2 mm
Density	75 kg/m³
Material	Made from latex impregnated needle felt
Brand	Luxerton
TOG rating	0.60 TOG
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Laying method	Floating
Product dimensions (Width)	130 cm
Product dimensions (Unit)	m²
Type of base floor	Fixed sand cement floor / Floating screed
Thermal resistance - R-value (Test method: ISO 8302)	0.060 m² K/W
Laying direction	Install Luxerton Standard under the carpet. Ensure that Luxerton Standard is at least 50 mm smaller than the back of the carpet.

Luxerton Standard 2 mm: 60 x 130 cm (27.30 m²)

Art. nr - 68071





