

Luxerton Standard 2 mm: 130 x 190 cm (34.58 m²)

Art. nr - 68072

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Luxerton Standard is a non-slip underlay made from latex impregnated needle felt. It is lightweight and creates a reliable base for any carpet. Free from harmful substances, it enhances the luxury and comfort of the carpet. Suitable for use on carpet, parquet, laminate, ceramics, cork, and PVC. Ideal for household use, easy to install, levels out small imperfections, extends the lifespan of the carpet, and is produced in an environmentally friendly way. Compatible with underfloor heating.

Luxerton Standard 2 mm: 130 x 190 cm (34.58 m²)

Art. nr - 68072

Specifications

| | |
|--|--|
| Floor type | Area rugs |
| Base unit | Box |
| Product weight | 150 g/m ² |
| Product dimensions (Length) | 130 cm |
| Product dimensions in m2 | 34.58 m ² |
| Thickness | 2 mm |
| Density | 75 kg/m ³ |
| Material | Made from latex impregnated needle felt |
| Brand | Luxerton |
| TOG rating | 0.60 TOG |
| Suitable for underfloor heating | Yes |
| Suitable for floor cooling | Yes |
| Domestic use | Yes |
| Laying method | Floating |
| Product dimensions (Width) | 190 cm |
| Product dimensions (Unit) | m ² |
| Type of base floor | Fixed sand cement floor / Floating screed |
| Thermal resistance - R-value (Test method: ISO 8302) | 0.060 m ² K/W |
| Laying direction | Install Luxerton Standard under the carpet. Ensure that Luxerton Standard is at least 50 mm smaller than the back of the carpet. |

Luxerton Standard 2 mm: 130 x 190 cm (34.58 m²)

Art. nr - 68072

estillon
WE WILL IMPROVE YOUR FLOOR

