Luxerton Standard 2 mm: 160 x 230 cm (36.8 m²)

Art. nr - 68073

Scan this QR code to view this product on our website.

Description

Luxerton Standard is a non-slip underlay made from latex-impregnated needle felt. This lightweight underlay creates a reliable foundation for any type of carpet. It is free from plasticizers and enhances the comfort and luxury of your carpet. Suitable for use on carpets, parquet, laminate, ceramic tiles, cork, and PVC. - Lightweight and easy to install - Levels out minor irregularities in the subfloor -Prolongs the lifespan and preserves the original appearance of the carpet - Environmentally friendly production - Suitable for use with underfloor heating







Specifications

Floor type	Area rugs
Base unit	Box
Product weight	150 g/m²
Product dimensions (Length)	160 cm
Product dimensions in m2	36.8 m ²
Thickness	2 mm
Density	75 kg/m³
Material	Made of latex impregnated needled felt
Brand	Luxerton
TOG rating	0.60 TOG
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Laying method	Floating
Product dimensions (Width)	230 cm
Product dimensions (Unit)	m²
Type of base floor	Fixed sand cement floor / Floating screed
Thermal resistance - R-value (Test method: ISO 8302)	0.060 m ² K/W
Laying direction	Install Luxerton Standard under the carpet. Ensure that Luxerton Standard is at least 50 mm smaller than the back of the carpet.

Luxerton Standard 2 mm: 160 x 230 cm (36.8 m²)

Art. nr - 68073





