

# Luxerton Standard 2 mm: 190 x 290 cm (38.57 m<sup>2</sup>)

Art. nr - 68074

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Luxerton Standard is a lightweight non-slip carpet underlay made from latex-impregnated needle felt that offers a solid foundation for any carpet. It contains no plasticizers and enhances the luxurious comfort of the carpet. Suitable for carpet, parquet, laminate, ceramics, cork, and PVC, making it ideal for home use. - Lightweight and easy to install - Levels out minor imperfections in the subfloor - Extends the lifespan and preserves the original appearance of the carpet - Environmentally friendly manufacturing - Compatible with underfloor heating

# Luxerton Standard 2 mm: 190 x 290 cm (38.57 m<sup>2</sup>)

Art. nr - 68074

## Specifications

Floor type	Area rugs
Base unit	Box
Product weight	150 g/m <sup>2</sup>
Product dimensions (Length)	190 cm
Product dimensions in m2	38.57 m <sup>2</sup>
Thickness	2 mm
Density	75 kg/m <sup>3</sup>
Material	Made of latex impregnated needled felt
Brand	Luxerton
TOG rating	0.60 TOG
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Laying method	Floating
Product dimensions (Width)	290 cm
Product dimensions (Unit)	m <sup>2</sup>
Type of base floor	Fixed sand cement floor / Floating screed
Thermal resistance - R-value (Test method: ISO 8302)	0.060 m <sup>2</sup> K/W
Laying direction	Install Luxerton Standard under the carpet. Ensure that Luxerton Standard is at least 50 mm smaller than the back of the carpet.

# Luxerton Standard 2 mm: 190 x 290 cm (38.57 m<sup>2</sup>)

Art. nr - 68074

**estillon**  
WE WILL IMPROVE YOUR FLOOR

