Art. nr - 68075



Scan this QR code to view this product on our website.





Description

Luxerton Standard is a non-slip underlay made from latex impregnated needle felt. This lightweight underlay creates a reliable base for any carpet. It contains no plasticizers and enhances the luxurious and comfortable feel of the carpet. Luxerton Standard is suitable for use on carpet, parquet, laminate, ceramic, cork, PVC and is ideal for household use. - Lightweight and easy to install - Levels small imperfections in the floor - Extends the lifespan and preserves the original appearance of the carpet - Environmentally friendly production - Suitable for use with underfloor heating

Luxerton Standard 2 mm: 240 x 340 cm (40.80 m²)

Art. nr - 68075



Specifications

Floor type	Area rugs
Base unit	Box
Product weight	150 g/m²
Product dimensions (Length)	240 cm
Product dimensions in m2	40.8 m ²
Thickness	2 mm
Density	75 kg/m³
Material	Made of latex impregnated needled felt
Brand	Luxerton
TOG rating	0.60 TOG
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Laying method	Floating
Product dimensions (Width)	340 cm
Product dimensions (Unit)	m²
Type of base floor	Fixed sand cement floor / Floating screed
Thermal resistance - R-value (Test method: ISO 8302)	0.060 m ² K/W
Laying direction	Install Luxerton Standard under the carpet. Ensure that Luxerton Standard is at least 50 mm smaller than the back of the carpet.

Luxerton Standard 2 mm: 240 x 340 cm (40.80 m²)

Art. nr - 68075





