Art. nr - 68076



Scan this QR code to view this product on our website.






Description

Luxerton Standard is a non-slip underlay made from latex-impregnated needle felt. This lightweight underlay provides a solid foundation for any carpet and is free from plasticizers, enhancing the luxury and comfort of the carpet experience. It is suitable for use on carpet, parquet, laminate, ceramics, cork, PVC, and is ideal for home use. - Lightweight and easy to install - Levels minor imperfections in the subfloor - Extends the lifespan and preserves the original look of the carpet - Environmentally friendly production - Compatible with underfloor heating

Luxerton Standard 2 mm: 40 x 1 m (40 m²)





Specifications

Floor type	Area rugs
Product weight	150 g/m²
Product dimensions (Length)	40 m
Product dimensions (Width)	1 m
Product dimensions in m2	40 m²
Base unit	Roll
Thickness	2 mm
Density	75 kg/m³
Brand	Luxerton
Laying method	Floating
Material	Made of latex impregnated needle felt
Product dimensions (Unit)	m²
TOG rating	0.60 TOG
Thermal resistance - R-value	0.060 m ² K/W
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Type of base floor	Fixed sand cement floor / Floating screed

Luxerton Standard 2 mm: 40 x 1 m (40 m²)

Art. nr - 68076



