Art. nr - 68077



Scan this QR code to view this product on our website.






## Description

Luxerton Standard is a non-slip underlay crafted from latex-impregnated needle felt. This lightweight underlay creates a stable foundation for any carpet and is free from plasticizers, enhancing the luxurious feel and comfort of your flooring. It is suitable for use on carpets, parquet, laminate, ceramics, cork, and PVC. - Lightweight and easy to install - Levels minor imperfections in the subfloor - Extends the lifespan and preserves the original look of the carpet - Environmentally friendly production - Suitable for use with underfloor heating

## Luxerton Standard 2 mm: 40 x 2 m (80 m<sup>2</sup>)





## **Specifications**

Floor type	Area rugs
Base unit	Roll
Product weight	150 g/m <sup>2</sup>
Product dimensions (Length)	40 m
Product dimensions in m2	80 m <sup>2</sup>
Thickness	2 mm
Density	75 kg/m <sup>3</sup>
Material	Made of latex impregnated needle felt
Brand	Luxerton
TOG rating	0.60 TOG
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Laying method	Floating
Product dimensions (Width)	2 m
Product dimensions (Unit)	m <sup>2</sup>
Type of base floor	Fixed sand cement floor / Floating screed
Thermal resistance - R-value (Test method: ISO 8302)	0.060 m <sup>2</sup> K/W
Laying direction	Install Luxerton Standard under the carpet. Ensure that Luxerton Standard is at least 50 mm smaller than the backing of the carpet.

## Luxerton Standard 2 mm: 40 x 2 m (80 m<sup>2</sup>)

Art. nr - 68077



