

# Black Magic 6 mm: 11 x 1,37 m (15,07 m<sup>2</sup>)

Art. nr - 681181

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Black Magic is an underlay made from 100% SBR rubber. This heavy rubber underlay provides a stable, comfortable, and durable foundation for any installation. Black Magic enhances the sense of luxury and comfort of the carpet. It is suitable for domestic, light commercial, and heavy contract use.

- Stable and easy to install
- Levels out minor irregularities in the subfloor
- Highly suitable for underfloor heating

# Black Magic 6 mm: 11 x 1,37 m (15,07 m<sup>2</sup>)

Art. nr - 681181

**estillon**  
WE WILL IMPROVE YOUR FLOOR

## Specifications

|                                       |   |
|---------------------------------------|---|
| Floor type                            | Carpet  |
| Product weight                        | 3500 g/m <sup>2</sup> (10% margin)  |
| Product dimensions (Length)           | 11 m (10% margin)   |
| Product dimensions (Width)            | 1.37 m  |
| Product dimensions in m2              | 15.07 m <sup>2</sup>  |
| Base unit                             | Roll  |
| Thickness                             | 6 mm (10% margin)   |
| Density                               | 584 kg/m <sup>3</sup> (10% margin)  |
| Material                              | Top layer: Fiber-reinforced non-woven<br>Middle layer: 100% SBR rubber<br>Bottom layer: Polyester non-woven |
| Brand                                 | Estillon  |
| TOG rating                            | 0.9 TOG   |
| Thermal resistance - R-value          | 0.09 m <sup>2</sup> K/W   |
| Suitable for underfloor heating       | Yes   |
| Suitable for floor cooling            | Yes   |
| Domestic use                          | Yes   |
| Project use                           | Yes   |
| Laying method                         | Tensioning / double-sided adhesive  |
| Type of base floor                    | Wooden floor / Fixed sand cement floor / Floating screed  |
| Wheelchair load (Test method: EN 985) | Suitable, provided it is double-sided glued   |

# Black Magic 6 mm: 11 x 1,37 m (15,07 m<sup>2</sup>)

Art. nr - 681181



|                               |                    |
|-------------------------------|--------------------|
| Sound-reducing - $\Delta L_w$ | 26 dB $\Delta L_w$ |
| Flame-retardant               | Bfl-S1             |

# Black Magic 6 mm: 11 x 1,37 m (15,07 m<sup>2</sup>)

Art. nr - 681181

**estillon**  
WE WILL IMPROVE YOUR FLOOR

