
Solidbase 2 mm: 8 x 1 m (8 m²)

Art. nr - 68135

Scan this QR code to view this product on our website.



Description

Solidbase 2 mm is a high-density underlay made from a combination of PU minerals laminated with a moisture barrier. It's designed for the installation of laminate and hardwood flooring for both residential and commercial environments.

- Improves impact sound
- Very high footfall sound reduction
- Suitable for both residential and commercial use
- High-pressure resistance
- 2-in-1 underlay with integrated moisture barrier
- For laminate and hardwood floors

Solidbase 2 mm: 8 x 1 m (8 m²)

Art. nr - 68135

Specifications

Floor type	Parquet / Laminate
Thickness	2 mm
Type of base floor	Fixed sand cement floor / Floating screed
Domestic use	Yes
Project use	Yes
PC (Punctual Conformability)	1.6
CS	CS3
CS/CC (compressive Strength / Compressive Creep)	> 250 kPa
Product weight	1560 g/m²
Product dimensions (Length)	8 m
Product dimensions (Width)	1 m
Product dimensions in m2	8 m²
Sound-reducing - ΔLw	18 dB ΔLw
TOG rating	0.1 TOG
Thermal resistance - R-value	0.01 m² K/W
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
SD (Steam Diffusion)	>150 micron
Fire classification	Bfl-s1
Flame-retardant - Test method	EN ISO 9239-1

Solidbase 2 mm: 8 x 1 m (8 m²)

Art. nr - 68135

Density	780 kg/m³
Material	Middle layer: Combination of PU/mineralsBottom layer: Aluminum moisture barrier
Brand	Solidbase
Laying method	Floating
Wheelchair load (Test method: EN 985)	Suitable
CS/CC (Compressive Strength / Compressive Creep)	> 250 kPa

Solidbase 2 mm: 8 x 1 m (8 m²)

Art. nr - 68135











