

Solidbase 2 mm: 8 x 1 m (8 m²)

Art. nr - 68135

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Solidbase 2 mm is a high-density underlay made from a combination of PU minerals laminated with a moisture barrier. It's designed for the installation of laminate and hardwood flooring for both residential and commercial environments.

- Improves impact sound
- Very high footfall sound reduction
- Suitable for both residential and commercial use
- High-pressure resistance
- 2-in-1 underlay with integrated moisture barrier
- For laminate and hardwood floors

Solidbase 2 mm: 8 x 1 m (8 m²)

Art. nr - 68135

Specifications

Floor type	Parquet / Laminate
Product weight	1560 g/m ²
Product dimensions (Length)	8 m
Product dimensions (Width)	1 m
Product dimensions in m2	8 m ²
Base unit	Roll
Thickness	2 mm
Density	780 kg/m ³
Material	Middle layer: Combination of PU/minerals Bottom layer: Aluminum moisture barrier
Brand	Solidbase
TOG rating	0.1 TOG
Thermal resistance - R-value	0.01 m ² K/W
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
SD (Steam Diffusion)	>150 micron
PC (Punctual Conformability)	1.6
CS	CS3
CS/CC (compressive Strength / Compressive Creep)	> 250 kPa
Domestic use	Yes

Solidbase 2 mm: 8 x 1 m (8 m²)

Art. nr - 68135

Project use	Yes
Laying method	Floating
Type of base floor	Fixed sand cement floor / Floating screed
Wheelchair load (Test method: EN 985)	Suitable
Sound-reducing - ΔL_w	18 dB ΔL_w
Flame-retardant	Bfl-S1
Flame-retardant - Test method	EN ISO 9239-1
CS/CC (Compressive Strength / Compressive Creep)	> 250 kPa

Solidbase 2 mm: 8 x 1 m (8 m²)

Art. nr - 68135

estillon
WE WILL IMPROVE YOUR FLOOR

