

# Normal felt 6mm. 35 x 2 m (70m<sup>2</sup>)

Art. nr - 68215

Scan this QR code to view this product on our website.



## Description

Cut-resistant needle felt underlayment made from brushed recycled textile fibers impregnated with latex. Designed for a durable installation.

- Offers excellent leveling ability
- Good indentation recovery
- Highly cut-resistant for quick and precise installation
- Extends the lifespan of the carpet

# Normal felt 6mm. 35 x 2 m (70m<sup>2</sup>)

Art. nr - 68215

## Specifications

Floor type	Carpet
Product weight	600 g/m <sup>2</sup> (10% margin)
Product dimensions (Length)	35 m (10% margin)
Product dimensions (Width)	2 m
Product dimensions in m2	70 m <sup>2</sup>
Base unit	Roll
Thickness	6 mm (10% margin)
Density	100 kg/m <sup>3</sup> (10% margin)
Material	Recycled needle felt
Brand	Estillon
TOG rating	2.3 TOG
Thermal resistance - R-value	0.23 m <sup>2</sup> K/W
Domestic use	Yes
Laying method	Stretch
DIBT certificate	Z-158.10-98
Green choice label	Yes
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Wheelchair load (Test method: EN 985)	Suitable
Sound-reducing - ΔLw	27 dB ΔLw
Sound-reducing - ΔLw - Test method	ISO 140-8:1998 / ISO 717-2:1997
Flame-retardant	Efl-S1

# Normal felt 6mm. 35 x 2 m (70m<sup>2</sup>)

Art. nr - 68215



Flame-retardant - Test method	EN ISO 9239-1
-------------------------------	---------------

# Normal felt 6mm. 35 x 2 m (70m<sup>2</sup>)

Art. nr - 68215

**estillon**  
WE WILL IMPROVE YOUR FLOOR



**estillon**  
GREEN CHOICE

