

# Non-skid PES Felt 1,5mm: 300 m x 3 m (900 m2)

Art. nr - 68234

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Non-skid PES felt is manufactured from 100% polyester with an acrylic anti-slip adhesive for industrial applications under carpets.

- Shrink-free, permanently anti-slip, suitable for underfloor heating
- Contains no plasticisers / 100% recyclable
- High-volume carpets / overlocking
- Production to order

# Non-skid PES Felt 1,5mm: 300 m x 3 m (900 m2)

Art. nr - 68234

**estillon**  
WE WILL IMPROVE YOUR FLOOR

## Specifications

Floor type	Area rugs
Product weight	127 g/m <sup>2</sup>
Product dimensions (Length)	300 m
Product dimensions (Width)	3 m
Product dimensions in m2	900 m <sup>2</sup>
Base unit	Roll
Thickness	1.5 mm
Density	85 kg/m <sup>3</sup>
Material	Polyester non-woven fleece
Brand	Estillon
TOG rating	0.6 TOG
Thermal resistance - R-value	0.06 m <sup>2</sup> K/W
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Project use	Yes
Laying method	Floating
Green choice label	Yes
Type of base floor	Fixed sand cement floor / Floating screed

# Non-skid PES Felt 1,5mm: 300 m x 3 m (900 m2)

Art. nr - 68234

**estillon**  
WE WILL IMPROVE YOUR FLOOR

