

Egalsoft 6,5 mm: 22 x 1,37 m (30,14 m²)

Art. nr - 68240

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Egalsoft® is a unique anti-slip underlay that ensures a durable and easy installation. The carpet underlay is an impregnated nonwoven material with a treated anti-slip surface. Egalsoft® is applicable for both residential and commercial installations. It provides luxury and comfort while extending the lifespan of the carpet. It features high indentation recovery and a removable system, making it perfect when nails or glue are not permitted. Additionally, it offers good sound reduction (27 dB) and thermal insulation. It is easy to cut and quick and simple to install.

Egalsoft 6,5 mm: 22 x 1,37 m (30,14 m2)

Art. nr - 68240

Specifications

Floor type	Carpet
Product weight	850 g/m ² (10% margin)
Product dimensions (Length)	22 m (10% margin)
Product dimensions (Width)	1.37 m
Product dimensions in m2	30.14 m ²
Base unit	Roll
Thickness	6.5 mm (10% margin)
Density	131 kg/m ³ (10% margin)
Material	Top layer: PP Spunbond / Middle layer: impregnated nonwoven / Bottom layer: anti-slip treated layer
Brand	Egalsoft
TOG rating	2.2 TOG
Thermal resistance - R-value	0.22 m ² K/W
VOC label	A+
Domestic use	Yes
Project use	Yes
Laying method	Stretching / single-sided bonding / double-sided bonding
DIBT certificate	Z-158.10-98
Green choice label	Yes
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Wheelchair load (Test method: EN 985)	Suitable

Egalsoft 6,5 mm: 22 x 1,37 m (30,14 m²)

Art. nr - 68240

Sound-reducing - ΔLw	27 dB ΔLw
Sound-reducing - ΔLw - Test method	ISO 10140-3:2010
Flame-retardant	Efl-S1
Dimensional stability tensile strength / Long / MD	> 7.0
Dimensional stability tensile strength / Long / MD - unit	kN/m
Dimensional stability tensile strength / Long / MD - Test method	DIN EN 10319
Dimensional stability tensile strength / Cross / CD	> 20.0
Dimensional stability tensile strength / Cross / CD- unit	kN/m
Dimensional stability tensile strength / Cross / CD - Test method	DIN EN 10319
Dimensional stability elongation / stretch / Long / MD	> 50

Egalsoft 6,5 mm: 22 x 1,37 m (30,14 m²)

Art. nr - 68240

estillon
WE WILL IMPROVE YOUR FLOOR

