

# Egalsoft 6.5 mm: 22 x 1.37 m (30.14 m<sup>2</sup>)

Art. nr - 68240

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Egalsoft® is a unique non-slip underlayment that ensures a durable and easy installation. The carpet underlay is an impregnated nonwoven material with a treated non-slip surface. Egalsoft® is applicable for both residential and commercial installations. It provides luxury and comfort while extending the lifespan of the carpet. It features high indentation recovery and a removable system, making it perfect when nails or glue are not permitted. Additionally, it offers good sound reduction (27 dB) and thermal insulation. It is easy to cut and quick and simple to install.

# Egalsoft 6.5 mm: 22 x 1.37 m (30.14 m<sup>2</sup>)

Art. nr - 68240

## Specifications

Floor type	Carpet
Base unit	Roll
Product weight	850 g/m <sup>2</sup>
Product dimensions (Length)	22 m
Product dimensions in m <sup>2</sup>	30.14 m <sup>2</sup>
Thickness	6.5 mm
Density	131 kg/m <sup>3</sup>
Material	Top layer: PP Spunbond Middle layer: impregnated nonwoven Bottom layer: anti-slip treated layer
Brand	Egalsoft
TOG rating	2.20 TOG
VOC label	A+
Dimensional stability tensile strength / Long / MD - unit	kN/m
Dimensional stability tensile strength / Cross / CS - unit	kN/m
Dimensional stability elongation / stretch / Long / MD - unit	%
Dimensional stability elongation / stretch / Across / CS - unit	%
Domestic use	Yes
Project use	Yes

# Egalsoft 6.5 mm: 22 x 1.37 m (30.14 m<sup>2</sup>)

Art. nr - 68240

Laying method	Stretching / single-sided bonding / double-sided bonding
Product dimensions (Width)	1.37 m
Product dimensions (Unit)	m <sup>2</sup>
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Wheelchair load (Test method: EN 985)	Suitable
Thermal resistance - R-value (Test method: ISO 8302)	0.220 m <sup>2</sup> K/W
Sound-reducing L <sub>w</sub> (Test method: NEN-EN ISO 717-2)	27 dB L <sub>w</sub>
Flame-retardant (Test method: EN 13501-1)	Efl-S1
Dimensional stability tensile strength / Long / MD; (Test method: DIN EN 10319)	> 7.0
Dimensional stability tensile strength / Cross / CD (Test method: DIN EN 10319)	> 20.0
Dimensional stability elongation / stretch / Long / MD; (Test method: DIN EN 10319)	> 50
Dimensional stability elongation / stretch / Across / CD (Test method: DIN EN 10319)	> 20
Laying direction	Perpendicular to the carpet installation direction. Avoid aligning the seams of the underlay and carpet.
Suitable for stair installation	Yes
DIBT certificate	Z-158.10-98
Green Choice	Yes

# Egalsoft 6.5 mm: 22 x 1.37 m (30.14 m<sup>2</sup>)

Art. nr - 68240

**estillon**  
WE WILL IMPROVE YOUR FLOOR

