Egalsoft 4 mm: 10 x 1.37 m (13.7 m²)

Art. nr - 68243

Scan this QR code to view this product on our website.



Description

Egalsoft® is a distinctive anti-slip underlay designed to ensure lasting and easy installation. This underlay is made from impregnated nonwoven material with an anti slip treated layer.

Egalsoft® is suitable for both domestic and commercial settings, providing a luxurious feel and added comfort while extending the lifespan of your carpet. Its high resilience helps the carpet retain its appearance for longer.

The removable system is ideal for areas where nails or adhesives cannot be used.

Additionally, it offers excellent sound reduction (27 dB) and thermal insulation. The underlay is simple to cut and quick to install.

Egalsoft 4 mm: 10 x 1.37 m (13.7 m²)

Art. nr - 68243

Specifications

Floor type	Carpet
Thickness	4 mm (10% margin)
Product weight	600 gr/m² (10% margin)
Density	131 kg/m³ (10% margin)
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Domestic use	Yes
Wheelchair load	Suitable, double stick only
Sound-reducing - ΔLw	27 dB ΔLw
TOG rating	1,5 TOG
Thermal resistance - R-value	0,15 m² K/W
Fire classification	Efl
VOC label	A+
Green choice label	Yes
Brand	Egalsoft
Laying method	Stretching / single-sided bonding / double-sided bonding
Product dimensions (Length)	30 m (10% margin)
Product dimensions (Width)	1,37 m
Product dimensions in m2	41,1 m²
Base unit	Roll
Material	Top layer: PP Spunbond / Middle layer: impregnated nonwoven / Bottom layer: anti-slip treated layer

Egalsoft 4 mm: 10 x 1.37 m (13.7 m²)

Art. nr - 68243

Sound-reducing - ΔLw - Test method	ISO 10140-3:2010