

Egalsoft FR 6 mm: 22 x 1.37 m (30.14 m²)

Art. nr - 68244

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Egalsoft FR® is a unique fire-retardant anti-slip underlay that provides a durable and easy installation. The underlay is an impregnated nonwoven material with an anti-slip treated layer, ideal for both residential and commercial applications.

Specifications

Floor type	Carpet
Base unit	Roll
Product weight	850 g/m ²
Product dimensions (Length)	22 m
Product dimensions in m2	30.14 m ²
Thickness	6 mm
Density	141 kg/m ³
Material	Top layer: PP Spunbond Middle layer: impregnated nonwoven Bottom layer: anti-slip treated layer
Brand	Egalsoft
TOG rating	2.20 TOG
VOC label	A+
Dimensional stability tensile strength / Long / MD - unit	kN/m
Dimensional stability tensile strength / Cross / CS - unit	kN/m
Dimensional stability elongation / stretch / Long / MD - unit	%
Dimensional stability elongation / stretch / Across / CS - unit	%
Domestic use	Yes
Project use	Yes

Egalsoft FR 6 mm: 22 x 1.37 m (30.14 m²)

Art. nr - 68244

Laying method	Stretching / single-sided bonding / double-sided bonding
Product dimensions (Width)	1.37 m
Product dimensions (Unit)	m ²
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Wheelchair load (Test method: EN 985)	Suitable
Thermal resistance - R-value (Test method: ISO 8302)	0.220 m ² K/W
Sound-reducing L _w (Test method: NEN-EN ISO 717-2)	27 dB L _w
Flame-retardant (Test method: EN 13501-1)	Bfl-S1
Dimensional stability tensile strength / Long / MD; (Test method: DIN EN 10319)	> 7.0
Dimensional stability tensile strength / Cross / CD (Test method: DIN EN 10319)	> 20.0
Dimensional stability elongation / stretch / Long / MD; (Test method: DIN EN 10319)	> 50
Dimensional stability elongation / stretch / Across / CD (Test method: DIN EN 10319)	> 20
Laying direction	Perpendicular to the carpet installation direction. Avoid aligning the seams of the underlay and carpet.
Suitable for stair installation	Yes
DIBT certificate	Z-158.10-98
Green Choice	Yes

Egalsoft FR 6 mm: 22 x 1.37 m (30.14 m²)

Art. nr - 68244

estillon
WE WILL IMPROVE YOUR FLOOR

