Egalsoft FR 6 mm: 22 x 1.37 m (30.14 m²)

Art. nr - 68244

Scan this QR code to view this product on our website.



Description

Egalsoft FR® is a unique fire-retardant anti-slip underlay that provides a durable and easy installation.

The underlay is an impregnated nonwoven material with an anti-slip treated layer, ideal for both residential and commercial applications.

Egalsoft FR 6 mm: 22 x 1.37 m (30.14 m²)

Art. nr - 68244

Specifications

Floor type	Carpet
Thickness	6 mm (10% margin)
Product weight	900 g/m² (10% margin)
Density	150 kg/m³ (10% margin)
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Domestic use	Yes
Project use	Yes
Wheelchair load (Test method: EN 985)	Suitable
Sound-reducing - ΔLw	27 dB ΔLw
TOG rating	2.2 TOG
Thermal resistance - R-value	0.22 m² K/W
Fire classification	Bfl-s1
Flame-retardant - Test method	EN 13501-1
VOC label	A+
Green choice label	Yes
DIBT certificate	Z-158.10-98
Brand	Egalsoft
Laying method	Stretching / single-sided bonding / double-sided bonding
Product dimensions (Length)	22 m (10% margin)
Product dimensions (Width)	1.37 m
Product dimensions in m2	30.14 m²

Egalsoft FR 6 mm: 22 x 1.37 m (30.14 m²)

Art. nr - 68244

Base unit	Roll
Material	Top layer: PP Spunbond / Middle layer: impregnated nonwoven / Bottom layer: anti-slip treated layer
Dimensional stability tensile strength / Long / MD	> 7.0
Dimensional stability tensile strength / Long / MD - unit	kN/m
Dimensional stability tensile strength / Long / MD - Test method	DIN EN 10319
Dimensional stability tensile strength / Cross / CD	> 20.0
Dimensional stability tensile strength / Cross / CD- unit	kN/m
Dimensional stability tensile strength / Cross / CD - Test method	DIN EN 10319
Dimensional stability elongation / stretch / Long / MD	> 50

Egalsoft FR 6 mm: 22 x 1.37 m (30.14 m²)

Art. nr - 68244





















