

Timbermate Excel DIY 3.6 mm: 14.6 x 0.685 m (10 m²)

Art. nr - 68585

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Sound-reducing underlay for laminate and parquet. Duralay Timbermate Excel is part of the Timbermate underlay collection alongside Silentfloor Gold. Timbermate Excel reduces noise in the room by up to 30% and includes an alu-foil to prevent moisture. Reduces noise by up to 30%
Specialized underlay for parquet and laminate Quick and easy to install Includes moisture barrier

Timbermate Excel DIY 3.6 mm: 14.6 x 0.685 m (10 m²)

Art. nr - 68585

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Floor type	Parquet / Laminate
Base unit	Roll
Product weight	2545 g/m ²
Product dimensions (Length)	14.6 m
Product dimensions in m2	10 m ²
Thickness	3.6 mm
Density	707 kg/m ³
Material	Sponge rubber
Brand	Duralay
TOG rating	0.55 TOG
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
CS/CC (compressive Strength / Compressive Creep)	43.1
CS/CC (compressive Strength / Compressive Creep) - unit	kPa
Domestic use	Yes
Laying method	Floating
Product dimensions (Width)	0.685 m
Product dimensions (Unit)	m ²
Type of base floor	Fixed sand cement floor / Floating screed

Timbermate Excel DIY 3.6 mm: 14.6 x 0.685 m (10 m²)

Art. nr - 68585

Thermal resistance - R-value (Test method: ISO 8302)	0.055 m ² K/W
Sound-reducing Lw (Test method: NEN-EN ISO 717-2)	23 dB Lw
Flame-retardant (Test method: EN 13501-1)	Cfl-S1
CS/CC (Compressive Strength / Compressive Creep)	43.1
CS/CC (Compressive Strength / Compressive Creep) - unit	kPa
Laying direction	Perpendicular to the laying direction of the upper floor. Prevent the seams of the undercarpet and upper floor from coinciding.

Timbermate Excel DIY 3.6 mm: 14.6 x 0.685 m (10 m²)

Art. nr - 68585

estillon
WE WILL IMPROVE YOUR FLOOR

