

Scan this QR code to view this product on our website.



Description

Sound-reducing underlay for laminate and parquet. Duralay Timbermate Excel is part of the Timbermate underlay collection alongside Silentfloor Gold. Timbermate Excel reduces noise in the room by up to 30% and includes an alu-foil to prevent moisture.

- Reduces noise by up to 30%
- Specialized underlay for parquet and laminate
- Quick and easy to install Includes moisture barrier

Specifications

| | |
|--|---|
| Floor type | Parquet / Laminate |
| Product weight | 2545 g/m ² |
| Product dimensions (Length) | 14.6 m |
| Product dimensions (Width) | 0.685 m |
| Product dimensions in m2 | 10 m ² |
| Base unit | Roll |
| Thickness | 3.6 mm |
| Density | 707 kg/m ³ |
| Material | Sponge rubber |
| Brand | Duralay |
| TOG rating | 0.55 TOG |
| Thermal resistance - R-value | 0.055 m ² K/W |
| Suitable for underfloor heating | Yes |
| Suitable for floor cooling | Yes |
| CS/CC (compressive Strength / Compressive Creep) | 43.1 kPa |
| Domestic use | Yes |
| Laying method | Floating |
| Type of base floor | Fixed sand cement floor / Floating screed |
| Sound-reducing - ΔLw | 23 dB ΔLw |
| Flame-retardant | Cfl-S1 |
| CS/CC (Compressive Strength / Compressive Creep) | 43.1 kPa |

Timbermate Excel DIY 3,6 mm: 14,6 x 0,685m (10 m2)

Art. nr - 68585

estillon
WE WILL IMPROVE YOUR FLOOR

