

Scan this QR code to view this product on our website.



Description

Sound-reducing underlay for laminate and parquet. Duralay Timbermate Excel is part of the Timbermate underlay collection alongside Silentfloor Gold. Timbermate Excel reduces noise in the room by up to 30% and includes an alu-foil to prevent moisture.

- Reduces noise by up to 30%
- Specialized underlay for parquet and laminate
- Quick and easy to install Includes moisture barrier

Specifications

Floor type	Parquet / Laminate
Thickness	3.6 mm
Type of base floor	Fixed sand cement floor / Floating screed
Domestic use	Yes
CS/CC (compressive Strength / Compressive Creep)	43.1 kPa
Product weight	2545 g/m ²
Product dimensions (Length)	14.6 m
Product dimensions (Width)	0.685 m
Product dimensions in m2	10 m ²
Sound-reducing - ΔLw	23 dB ΔLw
TOG rating	0.55 TOG
Thermal resistance - R-value	0.055 m ² K/W
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Flame-retardant	Cfl-S1
Density	707 kg/m ³
Material	Sponge rubber
Brand	Duralay
Laying method	Floating
Installation instruction explanation	Install with the aluminium side facing up.
CS/CC (Compressive Strength / Compressive Creep)	43.1 kPa

Timbermate Excel DIY 3,6 mm: 14,6 x 0,685m (10 m2)

Art. nr - 68585

estillon
WE WILL IMPROVE YOUR FLOOR

