

# Timbermate Excel 3.6 mm: 11 x 1.37 m (15.07 m<sup>2</sup>)

Art. nr - 68589

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Sound reducing underlayment for laminate and hardwood. Duralay Timbermate Excel, along with Silentfloor Gold, is part of the Timbermate underlayment range. Timbermate Excel reduces noise in the space by up to 30% and features an aluminum foil to prevent moisture. Reduces noise by up to 30%  
Specialized underlayment for hardwood and laminate Quick and easy to install Includes a moisture barrier

# Timbermate Excel 3.6 mm: 11 x 1.37 m (15.07 m<sup>2</sup>)

Art. nr - 68589

**estillon**  
WE WILL IMPROVE YOUR FLOOR

## Specifications

Floor type	Parquet / Laminate
Base unit	Roll
Product weight	2545 g/m <sup>2</sup>
Product dimensions (Length)	11 m
Product dimensions in m2	15.07 m <sup>2</sup>
Thickness	3.6 mm
Density	707 kg/m <sup>3</sup>
Material	Sponge rubber
Brand	Duralay
TOG rating	0.55 TOG
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
CS/CC (compressive Strength / Compressive Creep)	43.1
CS/CC (compressive Strength / Compressive Creep) - unit	kPa
Domestic use	Yes
Laying method	Floating
Product dimensions (Width)	1.37 m
Product dimensions (Unit)	m <sup>2</sup>
Type of base floor	Fixed sand cement floor / Floating screed

# Timbermate Excel 3.6 mm: 11 x 1.37 m (15.07 m<sup>2</sup>)

Art. nr - 68589

Thermal resistance - R-value (Test method: ISO 8302)	0.055 m <sup>2</sup> K/W
Sound-reducing Lw (Test method: NEN-EN ISO 717-2)	23 dB Lw
Flame-retardant (Test method: EN 13501-1)	Cfl-S1
CS/CC (Compressive Strength / Compressive Creep)	43.1
CS/CC (Compressive Strength / Compressive Creep) - unit	kPa
Laying direction	Perpendicular to the laying direction of the upper floor. Prevent the seams of the undercarpet and upper floor from coinciding.

# Timbermate Excel 3.6 mm: 11 x 1.37 m (15.07 m<sup>2</sup>)

Art. nr - 68589

**estillon**  
WE WILL IMPROVE YOUR FLOOR

