

Woodstep 3 mm: 11 x 1 m (11 m²)

Art. nr - 68592

Scan this QR code to view this product on our website.



Description

Woodstep underlayment is a flat sponge rubber laminated with a fiber-reinforced aluminum moisture barrier. Woodstep has high compressive strength and creates a fully stable base for your wooden floor. Woodstep is suitable for laminate and parquet flooring for residential and heavy project use.

- Excellent acoustic improvement
- High compressive strength
- Very stable and easy to install
- Strong leveling capability
- Integrated vapor/moisture barrier

Woodstep 3 mm: 11 x 1 m (11 m²)

Art. nr - 68592

- Extremely suitable for underfloor heating

Woodstep 3 mm: 11 x 1 m (11 m²)

Art. nr - 68592

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Floor type	Parquet / Laminate
Product weight	2800 g/m ²
Product dimensions (Length)	11 m
Product dimensions (Width)	1 m
Product dimensions in m2	11 m ²
Base unit	Roll
Thickness	3 mm
Density	933 kg/m ³
Material	Sponge rubber
Brand	Estillon
TOG rating	0.52 TOG
Thermal resistance - R-value	0.052 m ² K/W
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
PC (Punctual Conformability)	PC1
CS	CS0
CS/CC (compressive Strength / Compressive Creep)	> 12 kPa
Domestic use	Yes
Project use	Yes
Laying method	Floating
Type of base floor	Fixed sand cement floor / Floating screed

Woodstep 3 mm: 11 x 1 m (11 m²)

Art. nr - 68592

Wheelchair load (Test method: EN 985)	Suitable
Sound-reducing - ΔL_w	17 dB ΔL_w
CS/CC (Compressive Strength / Compressive Creep)	> 12 kPa

Woodstep 3 mm: 11 x 1 m (11 m²)

Art. nr - 68592

estillon
WE WILL IMPROVE YOUR FLOOR

