

Woodstep 3 mm: 11 x 1 m (11 m²)

Art. nr - 68592

Scan this QR code to view this product on our website.



Description

Woodstep underlayment is a flat sponge rubber laminated with a fiber-reinforced aluminum moisture barrier. Woodstep has high compressive strength and creates a fully stable base for your wooden floor. Woodstep is suitable for laminate and parquet flooring for residential and heavy project use. Excellent acoustic improvement High compressive strength, very stable and easy to install Strong leveling capability Integrated vapor/moisture barrier Extremely suitable for underfloor heating

Woodstep 3 mm: 11 x 1 m (11 m²)

Art. nr - 68592

Specifications

Floor type	Parquet / Laminate
Base unit	Roll
Product weight	2800 g/m ²
Product dimensions (Length)	11 m
Product dimensions in m2	11 m ²
Thickness	3 mm
Density	933 kg/m ³
Material	Sponge rubber
Brand	Estillon
TOG rating	0.52 TOG
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
PC (Punctual Conformability)	PC1
CS	CS0
CS/CC (compressive Strength / Compressive Creep)	> 12
CS/CC (compressive Strength / Compressive Creep) - unit	kPa
Domestic use	Yes
Project use	Yes
Laying method	Floating

Woodstep 3 mm: 11 x 1 m (11 m²)

Art. nr - 68592

Product dimensions (Width)	1 m
Product dimensions (Unit)	m ²
Type of base floor	Fixed sand cement floor / Floating screed
Wheelchair load (Test method: EN 985)	Suitable
Thermal resistance - R-value (Test method: ISO 8302)	0.052 m ² K/W
Sound-reducing L _w (Test method: NEN-EN ISO 717-2)	17 dB L _w
CS/CC (Compressive Strength / Compressive Creep)	> 12
CS/CC (Compressive Strength / Compressive Creep) - unit	kPa
Laying direction	Perpendicular to the direction of the top floor. Avoid having the seams of the underlay and the top floor coincide.

Woodstep 3 mm: 11 x 1 m (11 m²)

Art. nr - 68592

