


# Duralay Technics 5 mm: 11 x 1,37 m (15,07 m2)

Art. nr - 68616

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Duralay Technics is a flat sponge underlay that utilizes the unique Textron® backing to provide exceptional dimensional stability, making it ideal for project use.

- Suitable for the double-stick method
- Durable sponge rubber
- Proven reliability for project installations

# Duralay Technics 5 mm: 11 x 1,37 m (15,07 m2)

Art. nr - 68616

**estillon**  
WE WILL IMPROVE YOUR FLOOR

## Specifications

Floor type	Carpet
Product weight	2712 g/m <sup>2</sup>
Product dimensions (Length)	11 m
Product dimensions (Width)	1.37 m
Product dimensions in m2	15.07 m <sup>2</sup>
Base unit	Roll
Thickness	5 mm
Density	542.4 kg/m <sup>3</sup>
Material	Sponge rubber
Brand	Duralay
TOG rating	0.56 TOG
Thermal resistance - R-value	0.056 m <sup>2</sup> K/W
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Domestic use	Yes
Project use	Yes
Laying method	Stretch / double-sided bonding
DIBT certificate	Z-158.10-260
Type of base floor	Fixed sand cement floor / Floating screed
Sound-reducing - ΔLw	29 dB ΔLw
Flame-retardant	Bfl-S1

# Duralay Technics 5 mm: 11 x 1,37 m (15,07 m<sup>2</sup>)

Art. nr - 68616

**estillon**  
WE WILL IMPROVE YOUR FLOOR

