Duralay Technics 5 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 68616

Scan this QR code to view this product on our website.



Description

Duralay Technics is a flat sponge underlay that utilizes the unique Textron® backing to provide exceptional dimensional stability, making it ideal for project use.

- Suitable for the double-stick method
- Durable sponge rubber
- Proven reliability for project installations

Duralay Technics 5 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 68616

Specifications

Floor type	Parquet / Laminate / Carpet
Thickness	5 mm
Type of base floor	Fixed sand cement floor / Floating screed
Domestic use	Yes
Project use	Yes
Product weight	2712 g/m²
Product dimensions (Length)	11 m
Product dimensions (Width)	1.37 m
Product dimensions in m2	15.07 m²
Sound-reducing - ΔLw	29 dB ΔLw
TOG rating	0.56 TOG
Thermal resistance - R-value	0.056 m² K/W
DIBT certificate	Z-158.10-260
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Fire classification	Bfl-s1
Density	542.4 kg/m³
Material	Sponge rubber
Brand	Duralay
Laying method	Carpet: Stretch / double-sided bonding - Parquet & Laminate: Floating

Duralay Technics 5 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 68616

