Duralay Technics 6 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 68620

Scan this QR code to view this product on our website.



Description

The complete solution for project carpet installation. Technics is a flat sponge underlay that utilizes the unique Textron® backing to offer exceptional dimensional stability, making it ideal for project use. Suitable for double-stick method Durable sponge rubber Proven reputation for project installations

Duralay Technics 6 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 68620

Specifications

Floor type	Carpet
Thickness	6 mm (10% margin)
Product weight	3153 g/m² (10% margin)
Density	525.45 kg/m³ (10% margin)
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Domestic use	Yes
Project use	Yes
Sound-reducing - ΔLw	34 dB ΔLw
TOG rating	0.66 TOG
Thermal resistance - R-value	0.066 m² K/W
Fire classification	Bfl-s1
DIBT certificate	Z-158.10-260
Brand	Duralay
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Laying method	Stretch / double-sided bonding
Product dimensions (Length)	11 m (10% margin)
Product dimensions (Width)	1.37 m
Product dimensions in m2	15.07 m²
Base unit	Roll
Material	Sponge rubber

Duralay Technics 6 mm: 11 x 1.37 m (15.07 m²)

Art. nr - 68620



















