

PE Silver 2 mm: 15 x 1 m (15m²)

Art. nr - 68815

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

PE Silver is a PE foam laminated with a reinforced aluminum moisture barrier. PE Silver offers high compressive strength and creates a completely flat and smooth surface. It is suitable for laminate and parquet flooring for residential use.

- Excellent acoustic improvement
- Stable and easy to install
- Integrated vapor/moisture barrier with 50 mm flap and tape
- Compatible with underfloor heating

PE Silver 2 mm: 15 x 1 m (15m²)

Art. nr - 68815

Specifications

| | |
|--|---|
| Floor type | Parquet / Laminate |
| Thickness | 2 mm |
| Type of base floor | Fixed sand cement floor / Floating screed |
| Domestic use | Yes |
| PC (Punctual Conformability) | > 0.5 mm |
| CS | CS0 |
| CS/CC (compressive Strength / Compressive Creep) | > 10 kPa |
| Product weight | 40 g/m ² |
| Product dimensions (Length) | 15 m |
| Product dimensions (Width) | 1 m |
| Product dimensions in m ² | 15 m ² |
| Sound-reducing - ΔL_w | 20 dB ΔL_w |
| TOG rating | 0.67 TOG |
| Thermal resistance - R-value | 0.067 m ² K/W |
| DIBT certificate | Z-158.10-79 |
| Suitable for underfloor heating | Yes |
| Suitable for floor cooling | Yes |
| SD (Steam Diffusion) | 20 micron |
| Density | 20 kg/m ³ |

PE Silver 2 mm: 15 x 1 m (15m²)

Art. nr - 68815

| | |
|--|--|
| Material | Top layer: Non-woven polyethylene flat foam / Bottom layer: Metalized polypropylene 20 micron vapor/moisture barrier |
| Brand | Estillon |
| VOC label | A+ |
| Laying method | Floating |
| Wheelchair load (Test method: EN 985) | Suitable |
| CS/CC (Compressive Strength / Compressive Creep) | > 10 kPa |

PE Silver 2 mm: 15 x 1 m (15m²)

Art. nr - 68815

estillon
WE WILL IMPROVE YOUR FLOOR

