

# Black Uni B1 1,5 mm: 30 x 1 m (30 m<sup>2</sup>)

Art. nr - 68824

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Black Uni is an underlay made from high-density PU/cork granulate. Suitable for the installation of LVT Dryback, LVT Click, composite, laminate and wooden floors in both residential and commercial areas. Black Uni is a universal product for all types of floor coverings.

- Acoustically insulating underlay with very good sound insulation values
- Low emission values
- Also available with a Bfl-s1 certificate
- High density
- Suitable for underfloor heating
- Meets the enhanced requirements of CEN/TS 16354 from EPLF/MMFA
- Anti slip properties on both sides to support click connections

# Black Uni B1 1,5 mm: 30 x 1 m (30 m<sup>2</sup>)

Art. nr - 68824

**estillon**  
WE WILL IMPROVE YOUR FLOOR

## Specifications

Floor type	LVT Rigid Click / LVT Click / Laminate / Linoleum / Parquet / Rugs / Carpet tiles / Vinyl
Product weight	825 gr/m <sup>2</sup>
Product dimensions (Length)	30 m
Product dimensions (Width)	1 m
Product dimensions in m <sup>2</sup>	30 m <sup>2</sup>
Base unit	Roll
Thickness	1,5 mm
Density	550 kg/m <sup>3</sup>
Material	PU / cork granulate
Wheelchair load	Suitable
TOG rating	0,30 TOG
Thermal resistance - R-value	0,030 m <sup>2</sup> K/W
CS	CS3
CS/CC (compressive Strength / Compressive Creep)	> 400 kPa
Laying method	Floating / double-sided glue-down
Installation instruction explanation	Perpendicular to the laying direction of the top floor. Prevent the joints of the underlay and the top floor from aligning.
Green choice label	Yes
Sound-reducing - ΔLw	16 dB ΔLw
Flame-retardant	Bfl-S1

# Black Uni B1 1,5 mm: 30 x 1 m (30 m<sup>2</sup>)

Art. nr - 68824

**estillon**  
WE WILL IMPROVE YOUR FLOOR

