

Soundstop LVT AS 1 mm: 15 x 1 m (15 m²)

Art. nr - 68833

estillon
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



Description

Soundstop LVT AS 1 mm is a high-density PE foam with a slip-resistant layer. It offers excellent compressive strength and provides a completely smooth foundation for LVT Click flooring. It is suitable for LVT Click, laminate, parquet, LVT Rigid, and LVT Rigid with an underlay for both residential and commercial use.

- Very high compressive strength (CS > 999 kPa/m²)
- Slip-resistant surface
- Moisture barrier
- Suitable for underfloor heating

Soundstop LVT AS 1 mm: 15 x 1 m (15 m²)

Art. nr - 68833

estillon
WE WILL IMPROVE YOUR FLOOR

Specifications

Floor type	LVT Click / Laminate / Parquet / LVT Rigid Click / LVT Rigid with underlayment
Thickness	1 mm
Type of base floor	Fixed sand cement floor / Floating screed
Domestic use	Yes
Project use	Yes
PC (Punctual Conformability)	> 0.5 mm
CS	CS3
CS/CC (compressive Strength / Compressive Creep)	> 999 kPa
Product weight	300 g/m ²
Product dimensions (Length)	15 m
Product dimensions (Width)	1 m
Product dimensions in m ²	15 m ²
Sound-reducing - ΔLw	21 dB ΔLw
TOG rating	0.15 TOG
Thermal resistance - R-value	0.015 m ² K/W
DIBT certificate	Z-158.10-79
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
Flame-retardant	Efl-S1

Soundstop LVT AS 1 mm: 15 x 1 m (15 m²)

Art. nr - 68833

Flame-retardant - Test method	EN ISO 9239-1
Density	300 kg/m ³
Material	Top layer: non-slip layer Bottom layer: PE foam with high density
Brand	Soundstop
VOC label	A+
Laying method	Floating
Wheelchair load (Test method: EN 985)	Suitable
CS/CC (Compressive Strength / Compressive Creep)	> 999 kPa

Soundstop LVT AS 1 mm: 15 x 1 m (15 m²)

Art. nr - 68833

estillon
WE WILL IMPROVE YOUR FLOOR

