

Scan this QR code to view this product on our website.



## Description

Oceanbase Contract FR is produced from high-quality recycled polyurethane foam. This lightweight foam guarantees a stable and durable installation while increasing both the luxury and comfort of the carpet. Oceanbase Contract FR is designed for marine projects.

- Very high resilience
- Lightweight and easy to install
- Environmentally friendly production and 100% recycled material
- IMO certification

Install with PP non-woven facing upwards for double-sided bonding and the tension-fit method.

## Specifications

Floor type	Carpet
Thickness	6 mm (10% margin)
Product weight	909 g/m <sup>2</sup> (10% margin)
Density	151 kg/m <sup>3</sup> (10% margin)
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Domestic use	Yes
Project use	Yes
Wheelchair load (Test method: EN 985)	Suitable
Sound-reducing - $\Delta L_w$	28 dB $\Delta L_w$
TOG rating	1.8 TOG
Thermal resistance - R-value	0.18 m <sup>2</sup> K/W
Thermal resistance - Test method	BS 4745
Flame-retardant	Bfl-S1
Flame-retardant - Test method	ISO 9239-1:2002
IMO certificate	Yes
Green choice label	Yes
Brand	Best Base
Laying method	Stretching / double-sided adhesion
Product dimensions (Length)	11 m (10% margin)

# Oceanbase Contract FR 6 mm: 11 x 1,37 m (15,07 m<sup>2</sup>)

Art. nr - 71665



Product dimensions (Width)	1.37 m
Product dimensions in m2	15.07 m <sup>2</sup>
Base unit	Roll
Material	Top layer: Fire-retardant crepe / Middle layer: Rebond polyurethane foam / Bottom layer: PE film

# Oceanbase Contract FR 6 mm: 11 x 1,37 m (15,07 m<sup>2</sup>)

Art. nr - 71665

**estillon**  
WE WILL IMPROVE YOUR FLOOR

